

## High pressure cleaner

### MARI-CLEAN

### MS 300/42

#### Dual Pump System w/Booster Pump

Cold water

Stationary

3x440 V - 60 Hz



#### Technical Data

Pressure range	50-300 bar
Capacity	2 x 21 l/min
Water inlet connection	1 inch
HP outlet	3/4 inch.
Motor	2 x 13,2 kW
Voltage	3x440 V
Frequency	60 Hz
Length	880 mm
Width	580 mm
Height	1120 mm
Weight net.	290 kg

Booster pump Grundfoss CR

#### Description

MARI-CLEAN MS300/42 is a stationary high pressure cleaner in twin installation complete with 2 pumps, motor and start cabinet. All mounted on coated steel frame with lifting eyes and fitted with vibration dampers.

#### Equipped with

- Pressure regulator/overflow valve
- Safety Valve
- Pressure Gauge
- Water inlet filter 50my
- Flow switch
- Non-return valve
- One high pressure outlet
- Electrical panel with automatic star/delta starter
- By pass running after closing gun
- Hour counter
- Emergency stop
- Auto start/stop w /timer
- Booster pump on inlet side with automatic start/stop build in main start cabinet

#### Optional equipment

Part no.	Description
35.210.000	HP Gun 320 Bar
34.401.015	HP hose 3/8" x 15 mtr.
38.350.050	Rotonozzle 050
35.210.209	Lance for rotonozzle

